



# Machinery Parts



7006CTRUMP4Y Bearing 2D drawings and 3D CAD models

1.181 Inch | 30 Millimeter x 2.165 Inch | 55 Millimeter x 1.024 Inch | 26 Millimeter NSK 7006CTRUMP4Y Precision Ball Bearings

Bearing No. 7006CTRUMP4Y

Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	0.22
EAN	0029176580598
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7   ISO P4
Material - Ball	Steel
Number of Bearings	2 (1 Pair)
Contact Angle	15 Degree
Preload	Medium
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Mounting Arrangement	Duplex-Universal
Flush Ground	Yes
Inch - Metric	Metric
Other Features	Single Row   Angular Contact   Bore and OD are Exclusive All Others are ISO 4
Long Description	30MM Bore; 55MM Outside Diameter; 26MM Width; Open Enclosure;



## Machinery Parts

	ABEC 7   ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 15 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Rac
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Item Number	7006CTRDUMP4Y
Weight / LBS	0.485
B	1.024 Inch   26 Millimeter
d	1.181 Inch   30 Millimeter
D	2.165 Inch   55 Millimeter
bore diameter:	30 mm
radial static load capacity:	2310 lb
outside diameter:	55 mm
cage material:	Phenolic Resin
overall width:	13 mm
outer ring width:	13 mm
contact angle:	15 °
maximum rpm:	41200 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 7 (ISO Class 4)
closure type:	Open
fillet radius:	0.04 in
bearing material:	Steel (Balls)
series:	7000C



## Machinery Parts

radial dynamic load capacity:	3400 lb
----------------------------------	---------